

▶ 产品特点(Product Features):

尺寸(Size):Φ80X80X38mm

构造(Construction):

- ▶ 铝合金压铸件(Die-cast Aluminum Housing)
- ▶ 玻璃纤维增强塑料叶轮UL 94V-0评级
(Glass Fiber Reinforced Plastic Impeller, UL 94V-0 Rating)
- ▶ 阻抗保护(Impedance Protected)
- ▶ 引线或终端是可用的(Leader Wire Or Terminal Is Available)

温度范围(Operating Temperature):

- ▶ 滚珠轴承(Ball Bearing) -30°C to +75°C
- ▶ 含油轴承(Sleeve Bearing) -10°C to +70°C

重量(Weight):

- ▶ 340grams



▶ 产品特性参数 Specification

MODEL	BEARING	RATING	FREQUENCY	RATING	POWER	SPEED	AIR FLOW		STATIC	NOISE
		VOLTAGE		CURRENT						
		VAC	Hz	A	W	RPM	m³/min	CFM	mmH₂O	dB-A
8038B1H*	Ball	115	50/60	0.15/0.13	16.0/14.0	2400/2900	0.68/0.88	24/31	3.30/4.83	31/35
8038S1H*	Sleeve									
8038B1M*	Ball	115	50/60	0.13/0.11	14.0/12.0	2200/2400	0.62/0.65	22/23	3.10/3.60	27/31
8038S1M*	Sleeve									
8038B1L*	Ball	115	50/60	0.10/0.09	10.0/9.0	1800/1600	0.51/0.48	18/17	2.90/2.70	19/17
8038S1L*	Sleeve									
8038B2H*	Ball	220/240	50/60	0.11/0.10	18.0/16.0	2400/2900	0.68/0.88	24/31	3.30/4.83	31/35
8038S2H*	Sleeve									
8038B2M*	Ball	220/240	50/60	0.09/0.08	14.0/12.0	2200/2400	0.62/0.65	22/23	3.10/3.60	27/31
8038S2M*	Sleeve									
8038B2L*	Ball	220/240	50/60	0.08/0.07	10.0/9.0	1800/1600	0.51/0.48	18/17	2.90/2.70	19/17
8038S2L*	Sleeve									

*=T,L(T-Terminal type,L-Lead wire)

