



型号Model	M12-3F□L-02A-*		M12-3F□L-02AY-*	
	M12-4F□L-02C-*		M12-4F□L-02CY-*	
	M12-5F□L-02C-*		M12-5F□L-02CY-*	
	M12-8F□L-02C-*		M12-8F□L-02CY-*	
额定电压(最大电压) Rated voltage (maximum voltage)	3-Pin, 4-Pin	250V	3-Pin, 4-Pin, 4+PE	24VDC
	5-Pin	60V		
	8-Pin	30V		
电流负荷(最大电流) Current load (maximum current)	3-Pin,4-Pin,5-Pin	4A	3-Pin, 4-Pin, 4+PE	4A
	8-Pin	2A		
绝缘电阻 Insulation resistance	≥10 ⁸ Ω			
材质Material	压头Indenter		TPU(黑色,棕色等) .PP白色/TPU Black, Brown, etc.PP white	
	触头载体Contact carrier		PA(黑色,棕色等) .PP白色/PA Black, Brown, etc.PP white	
	密封圈Sealing ring		FPM/FKM	
	触点Contact point		铜锌,镀金Copper zinc. Gold plated	
	锁紧机构Locking mechanism		铜锌,镀镍,不锈钢Copper zinc. Nickel plated. Stainless steel	
环境温度 Ambient temperature	标准型：-25℃/+70℃ 耐温型：-40℃/+150℃			
防护等级（拧紧状态） Protection level (tightened state)	IP67			
机械寿命周期 Mechanical cycle	>150拔插次数> 150 pull outs			
孔头（母头）编码 Hole(female connector)coding	1.棕色2.白色3.蓝色4.黑色（粉红色）5.灰色6.黄色7.绿色8.红色 1. brown 2. white 3. blue 4. Black(pink)5.gray6.yellow7.green8.red			
排列图	3针  1:BN 3:BU 4:BK 4针  1:BN 2:WH 3:BU 4:BK 4针+PE  1:BN 5:GNYE 2:WH 3:BU 4:BK 5针  1:BN 5:GY 2:WH 3:BU 4:BK 8针  1:WH 5:GY 2:BN 6:PK 3:GN 7:BU 4:YE 8:RD		3针  1:BN 3:BU 4:BK 4针  1:BN 2:WH 3:BU 4:BK 4针+PE  1:BN 5:GNYE 2:WH 3:BU 4:BK	
Dimension(尺寸图)	 			