



型号 Model	M12-3M□L-02AY-*	
	M12-4M□L-02CY-*	
	M12-5M□L-02CY-*	
	M12-8M□L-02CY-*	
额定电压 (最大电压) Rated voltage(maximum voltage)	3, 4	250V
	4+PE,5	60V
	8	30V
电流负荷 (最大电流) Current load(maximum current)	3, 4, 4+PE.5	4A
	8	2A
绝缘电阻 Insulation resistance	≥10 ⁸ Ω	
材质 Material	压头 Indenter	TPU(黑色.棕色等) .pp白色 Black, Brown, etc.ppwhite
	触头载体 Contact carrier	PA(黑色.棕色等) .pp白色 Black, Brown, etc.ppwhite
	密封圈 Sealing ring	FPM/FKM
	触点 Contact point	铜锌 镀金 Copper zinc. Gold plated
	锁紧机构 Locking mechanism	铜锌 镀镍.不锈钢 Copper zinc. Nickel plated. Stainless steel
环境温度 Ambient temperature	标准型 : -25°C/+70°C 耐温型 : -40°C/+150°C	
防护等级 (拧紧状态) Protection level (tightened state)	IP67,IP69	
机械寿命周期 Mechanical cycle	>150拔插次数 >150 pull outs	
孔头 (母头) 编码 Hole(female connector)coding	1.棕色2.白色3.蓝色4.黑色 (粉红色) 5.灰色6.黄色7.绿色8.红色 1. brown 2. white 3. blue 4. Black(pink)5.gray6.yellow7.green8.red	
排列图		
Dimension(尺寸图)		