

额定规格/性能Ratings and Specifications

标准型Standard

型号(Model)	DA-360-1BV	DA-±15-2BV
轴数(Axis number)	1轴axis	2轴axis
量程(Range) ①	0°~ 360°	X/Y轴axis:±15°
输出信号 (Output signal) ②	0.5~4.5V	
分辨率(Resolution)	0.01°	
精度(Accuracy)	±0.2°	
温度系数 (Temperature coefficient)	±0.01°/°C	
供电电压(Power supply)	10~30 VDC	
综合误差 (Comprehensive error)	±0.5%FS	
工作温度(Work temperature)	-40°C~ +85°C	
存储温度(Store temperature)	-40°C~ +125°C	
电气接口(Connection)	Cable(2m)标配2米导线	
外壳材料(Housing material)	ABS	
防护等级 (Protection degree)	IP67	
长期稳定性 (Long term stability)	±0.25%FS/1年(Year)	
耐振动(Anti-vibration)	9.8g(30HZ)	

①双轴角度量程0°~±180°范围可定制 Dual-axis angle 0°~180°customizable

②电流、电压输出可选 Current or voltage output optional

Dimension(尺寸图) (Unit/单位:mm)	Induction magnetic base (感应磁座) CAD数据
--------------------------------	--