

产品特点

- 测量范围:0~1.6MPa,0~3MPa ;
- 17-4PH或316L不锈钢隔离, 全不锈钢结构, 内带顶针 ;
- 高可靠性, 高过载能力;
- 温度范围广, 制冷设备专用;
- 7/16-20UNEF内螺纹;

Product Features

- Measuring range: 0-1.6 MPa, 0-3 MPa;
- 17-4PH or 316L stainless steel isolation, stainless steel structure with thimble inside;
- High reliability/high overload capability;
- Wide temperature range, used on refrigeration equipment;
- 7/16-20UNEF internal thread;



额定规格/性能 Ratings and Specifications

Type code(系列)	SDYW-C1
Pressure range(量程范围)	0-1.6MPa,0-3MPa
Pressure unit(压力单位)	M:MPa P:PSi B:bar
Accuracy(综合精度)	±0.5% FS
Shell material(壳体材质)	17-4PH/316L
Nipple structure(接口结构)	with thimble/内带顶针
Nipple type(接口方式)	7/16-20UNEF internal thread/7/16-20UNEF内螺纹
Temperature range(温度范围)	Wide range/温度范围广
Feature(产品特性)	High stability , high overload ability/高可靠性 ,高过载能力
Connection(电气连接方式)	C1:1m cable(1m电缆线), C2:2m cable(2m电缆线), XX:others(其它连接方式)
Dimension(尺寸图)	<p style="text-align: center;">CAD数据</p> <p>■ output: Red line:power Black line:current output</p>